



Jinan QiMing Bearing Co., Ltd.



NUP 215 ECM/C3 Bearing 2D drawings and 3D CAD models

2.953 Inch | 75 Millimeter x 5.118 Inch | 130 Millimeter x 0.984 Inch | 25 Millimeter SKF NUP 215 ECM/C3 Cylindrical Roller Bearings

Bearing No. NUP 215 ECM/C3

| | |
|---------------------------|---|
| Category | Cylindrical Roller Bearings |
| Inventory | 1.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 1.574 |
| EAN | 7316577035288 |
| Product Group | B04144 |
| Bore Profile | Straight |
| Cage Material | Brass |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | No |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C3-Loose |
| Retainer | Yes |
| Relubricatable | Yes |
| Inch - Metric | Metric |
| Other Features | High Capacity 1 Rib Inner Ring with Side Plate 2 Rib Outer Ring Cage on Outer Ring ID |
| Long Description | 75MM Bore; Straight Bore Profile; 130MM Outside |



Jinan QiMing Bearing Co., Ltd.

| | |
|--------------------------|--|
| | Diameter; 25MM Width; Brass Cage Material; RBEC 1 ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C3-Loose Internal Clearance; Retai |
| Category | Cylindrical Roller Bearing |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | NUP 215 ECM/C3 |
| Weight / LBS | 3.466 |
| d | 2.953 Inch 75 Millimeter |
| B | 0.984 Inch 25 Millimeter |
| D | 5.118 Inch 130 Millimeter |
| bore diameter: | 75 mm |
| static load capacity: | 156 kN |
| outside diameter: | 130 mm |
| precision rating: | Not Rated |
| overall width: | 25 mm |
| maximum rpm: | 6000 RPM |
| flanges: | (4) Flanges, Two-Piece Inner Ring |
| bearing material: | Steel |
| bore type: | Straight |
| cage material: | Brass |
| number of rows: | 1 |
| finish/coating: | Uncoated |
| internal clearance: | C3 |
| closure type: | Open |
| ring separation: | Separable Ring |
| outer ring width: | 25 mm |
| operating temperature | Maximum of +300 ° F |



Jinan QiMing Bearing Co., Ltd.

| | |
|------------------------|--------|
| range: | |
| fillet radius: | 1.5 mm |
| dynamic load capacity: | 150 kN |
| series: | NUP2 |