



# Jinan QiMing Bearing Co., Ltd.



SAKB 6 F Bearing 2D drawings and 3D CAD models

## SKF SAKB 6 F Spherical Plain Bearings - Rod Ends

Bearing No. SAKB 6 F

Category	Spherical Plain Bearings - Rod Ends
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.02
EAN	7316577003713
Product Group	B04286
Stud Profile	Male
Mounting Thread	M6 X 1
Thread Direction	Right Hand
Rolling Element	Spherical Plain
Material - Outer Member	Steel
Material - Ball	Steel
Material - Liner	Plastic   Teflon
Relubricatable	No
Enclosure	Open
Other Features	2 Piece   Zinc Plated Outer   Self Lubricating   Maintenance Free
Long Description	6MM Bore; 6.75MM House Width; Male Stud Profile; M6 X 1; Right Hand Thread Direction; Spherical Plain Bearing; Steel Outer Member; Steel Ball; Plastic
Inch - Metric	Metric
Category	Plain Bearing Spherical Rod



## Jinan QiMing Bearing Co., Ltd.

	Ends
UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55
Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	SAKB 6 F
Weight / LBS	0.046
Housing Width	0.266 Inch   6.75 Millimeter
d	0.236 Inch   6 Millimeter
Ball Width	0.354 Inch   9 Millimeter
bore diameter:	6 mm
ball material:	Steel
misalignment angle:	13 °
race material:	PTFE Composite
shank thread length:	21 mm
radial static load capacity:	6.8 kN
rod end type:	Male Threaded
operating temperature range:	-40 to +75 ° F
shank thread size:	M6
head diameter:	21 mm
thread direction:	Right Hand
head width:	6.75 mm
grade:	Commercial/Industrial
ball width:	9 mm
lubrication type:	Maintenance Free/Self-Lubricating
length to ball center:	36 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998, ISO 965-1:1998



## Jinan QiMing Bearing Co., Ltd.

d	6 mm
d <sub>2</sub> max.	21 mm
B	9 mm
G	M 6
C <sub>1</sub> max.	7.5 mm
h	36 mm
	17 °
d <sub>k</sub>	12.7 mm
l <sub>1</sub> min.	21 mm
l <sub>2</sub> max.	48 mm
r <sub>1</sub> min.	0.3 mm
Basic dynamic load rating C	4.25 kN
Basic static load rating C <sub>0</sub>	6.8 kN
Specific dynamic load factor K	50 N/mm <sup>2</sup>
Material constant K <sub>M</sub>	530
Mass rod end	0.021 kg